

## PIR DATA SHEET

---

### Retracom Supplies & Installs

PIR Cold store Insulated Panels.

<b>Core;</b>	PIR (Polyisocyanurate)
<b>Thickness;</b>	50mm 75mm 100mm 150mm 200mm
<b>Panel width;</b>	1200mm Kingspan, 1100mm Metecno
<b>Max Wall Heights;</b>	5.16m 6.40m 9.10m 12.15m 14.05m*
<b>Available Lengths;</b>	2m – 12m Lengths from 12 to 17.5 subject to additional transport charge.
<b>Steel Skins;</b>	Thickness- 0.5mm Kingspan, 0.6mm Metecno. Substrate- Zincform® G300s Z275 BFC steel Coating- Colorbond® Permaguard™ white Microban® anti bacterial additive 25% gloss
<b>Ribbing;</b>	Equi-Bead ,Flat, or Micro Rib
<b>BCA Classification;</b>	Group 2
<b>FM Approved:</b>	Factory Mutual (FM) approved to FMRC 4880 Class 1 Fire Classification (No Height restriction or unlimited Height)
<b>Applications;</b>	Walls & ceilings Satisfy's additional conditions & Insurer approvals when Building Code of Australia Requirements are to be exceeded.
<b>Warranty;</b>	Manufacturer's warranty on individual project basis.